



Level 1 550 Flinders Street
Melbourne Victoria 3000
1 300 642 427
1 300 305 606
admin@cprfirstaid.com.au
www.cprfirstaid.com.au

SAMARITAN 350P

COMPACT, EASY-TO-USE, LIFESAVING TECHNOLOGY

Sudden Cardiac Arrest (SCA) is a leading cause of death globally. Response time is critical for survival. The Samaritan® PAD 350P is designed especially for use in public areas by providing a sophisticated defibrillator for adult or Pediatric use, inside a lightweight and easy-to-operate system.

EASY-TO-FOLLOW GUIDES

User-friendly. The Samaritan PAD 350P features easy-to-understand visual and voice prompts that guide a user through the process including CPR coaching.

Two-button operation. Only two buttons, ON/OFF and SHOCK, are required for straightforward operation.

Always ready. A System Status Ready Indicator flashes to show that the complete system is operational and ready for use. The device automatically runs self-check each week. Providing a sophisticated




COMPACT IN SIZE, BIG ON ABILITY

Highest level of dust/moisture protection. The samaritan PAD has a rating of IP56, providing the 350P defibrillator with the highest level of protection from dust or moisture ingress in the industry.

Durable. The samaritan PAD 350P resists shock and vibration and comes with a shock-proof carry case free of charge

Advanced technology. The Samaritan PAD 350P utilizes proprietary electrode technology, advanced and stable firmware, and proprietary SCOPE™* Biphasic Technology to assess rhythm and recommend defibrillation is necessary.

*See overleaf for more information



PAD PAK TECHNOLOGY

Low cost of ownership.

Pad Pak cartridge has a shelf life of four years from date of manufacture, offering significant savings over other defibrillators that require separate battery and pad units



Two parts, one expiration date.

Cartridge combines battery and electrode pads, with one expiration date to monitor.

Great for children.

The HeartSine PAD's built-in intelligence and unique pediatric Pad-Pak ensure the appropriate energy level is delivered for children.



Level 1 550 Flinders Street
Melbourne Victoria 3000
1 300 642 427
1 300 305 606
admin@cprfirstaid.com.au
www.cprfirstaid.com.au

TECHNICAL SPECIFICATIONS



PHYSICAL WITH PAD-PAK™ INSERTED

Size:	20 cm x 18.4 cm x 4.8 cm
Weight:	1.1kg including Pad-Pak battery

DEFIBRILLATOR

Waveform:	Self-Compensating Output Pulse Envelope (SCOPE) Biphasic waveform. Optimized biphasic escalating waveform compensates energy, slope and envelope for patient impedance
-----------	--

PATIENT ANALYSIS SYSTEM

Method:	Evaluates patient's ECG, signal quality, electrode contact integrity and patient impedance to determine if defibrillation is required
Sensitivity/Specificity:	Meets ISO 60601-2-4

ENVIRONMENTAL

Operating/Standby Temperature:	0°C to 50°C
Temporary Transportation Temperature:	-10°C to 50°C for up to two days. Unit must be returned to standby/operating temperature for 24 hours before use.
Relative Humidity:	5% to 95% (non-condensing)
Water Resistance:	IEC 60529/EN 60529 IP56
Altitude:	0 – 4,575 meters
Shock:	MIL STD 810F Method 516.5, Procedure I (40 Gs)
Vibration:	MIL STD 810F Method 514.5+, Category 4 Truck Transportation – US Highways, Category 7 Aircraft – Jet 737 & General Aviation (Exposure)
EMC:	EN 60601-1-2
Radiated emissions:	EN55011
Electrostatic Discharge RF Immunity:	EN61000-4-3 80MHZ-2.5GHZ (10 V/m)
Magnetic Field Immunity:	EN61000-4-8 (3 A/m)
Aircraft:	RTCA/DO-160F, Section 21 (Category M)
Drop Tested:	1 metre

ENERGY SELECTION

Adult:	Shock 1: 150J; Shock 2: 150J; Shock 3: 200J
Paediatric:	Shock 1: 50J; Shock 2: 50J; Shock 3: 50J

CHARGING TIME

New Battery:	Typically 150J in < 8 seconds, 200J in < 12 seconds
After 6 Discharges:	Typically 150J in < 8 seconds, 200J in < 12 seconds

EVENT DOCUMENTATION

Type:	Internal Memory
Memory Capacity:	90 minutes of ECG (full disclosure) and event/incident recording
Playback capabilities:	Custom USB cable directly connected to PC and Saver™ EVO Windows-based data review software

MATERIALS USED

Housing:	ABS, Santoprene. Printed circuit board with electronic components.
Electrodes:	Hydrogel, Silver, Aluminium and Polyester

PAD PAK - ELECTRODE & BATTERY CARTRIDGE

Shelf Life:	4 years from manufacture date
Weight:	0.2kg
Size:	10 cm x 13.3 cm x 2.4 cm
Battery Type:	Lithium Manganese Dioxide (LiMnO ₂)
Capacity:	> 60 shocks at 200J 18V, 1.5 Amp Hrs
Electrodes:	HeartSine samaritan® disposable defibrillation pads are supplied as standard with each device
Placement:	Anterior-lateral (Adult); Anterior-posterior (Pediatric)
Active Gel Area:	100 cm ²
Cable Length:	1 metre



DID YOU KNOW

the HeartSine 350P has lower running costs than ANY other AED across its 8yr warranty period

